

# HOW TO USE YOUR GARDEN TOOL PACKAGE

**TURNING PLOW** – THE TURNING PLOW IS USED FOR BREAKING GROUND BY TURNING THE TOP SOIL UNDER EXPOSING FRESH DIRT TO THE SURFACE. THE PLOW MOUNTS TO THE TOOL BAR AS SHOWN IN ILLUSTRATION. WIDTH OF CUT MAY BE ADJUSTED BY SLIDING THE PLOW TO THE LEFT OR RIGHT ON THE TOOL BAR. THE FAR RIGHT POINT OF THE PLOW HEAD SHOULD OVERLAP THE INSIDE OF THE REAR TIRE BY AT LEAST 1/2". WHEN PLOWING OTHER THAN THE INITIAL FURROW, THE RIGHT FRONT AND REAR WHEEL OF THE TRACTOR ARE PLACED IN THE PREVIOUS FURROW. PLOWING DEPTH WILL BE DETERMINED BY THE POSITION OF TOPLINK (B). CLOCKWISE TURNS WILL MAKE A DEEPER FURROW. COUNTER CLOCKWISE WILL MAKE A SHALLOWER FURROW. AT LEAST FOUR FURROWS MUST BE PLOWED TO OBTAIN A DEPTH OF 6" OR MORE. THE FRONT POINT OF THE PLOW SHOULD BE LEVEL WHEN DESIRED DEPTH IS OBTAINED. ADJUST ACCORDINGLY WITH TOPLINK.

**DISC HARROW** – THE DISC HARROW MAY BE MOUNTED IN TWO DIFFERENT POSITIONS AS SHOWN IN THE ILLUSTRATION. ONE MOUNTING WILL THROW DIRT TO THE OUTSIDE. THE OPPOSITE MOUNTING WILL THROW DIRT TO THE MIDDLE. THE LATTER MOUNTING CAN BE USED FOR BUILDING HILLS FOR POTATOE OR MELON PLANTING. ADJUSTING THE TOPLINK WILL VARY THE AMOUNT OF SOIL THROWN TO THE HILL.

**CULTIVATORS** – MANY VARIATIONS OF THE TOOL BAR AND SHANKS MAY BE USED. SWEEPS OF VARIOUS TYPES AND SIZES MAY BE MOUNTED IN A STRAIGHT OR OFFSET PATTERN. PRIMARY USE OF THIS TOOL WILL BE FOR THE REMOVAL OF UNWANTED GROWTH OF WEEDS BETWEEN THE ROWS.

**MIDDLE BUSTERS-FURROWER** – USED PRIMARILY FOR FORMING HILLS AND LAYING OUT ROWS IN THE SOUTHERN STATES ONLY. CENTER ONE BUSTER DIRECTLY BEHIND THE CENTER OF EACH REAR TIRE. THIS WILL THROW THE DIRT TO THE MIDDLE LEAVING TWO FURROWS AND ONE HILL DIRECTLY IN THE CENTER OF THE TRACTOR. ON THE RETURN PASS, THE WHEELS ON ONE SIDE OF THE TRACTOR SHOULD BE PUT IN THE FURROW. THIS WILL ENABLE YOU TO KEEP ALL ROWS THE SAME DISTANCE APART. THE FURROWER, (SINGLE BUSTER) MAY BE USED FOR OPENING A SEED BED FOR PLANTING OR TAKING DOWN OLD HILLS AT THE END OF THE SEASON. POTATOE DIGGING IS ALSO POSSIBLE WITH THE FURROWER. REMEMBER, BY ADJUSTING THE TOP LINK, YOU CAN CONTROL THE DEPTH AS WELL AS THE AMOUNT OF DIRT YOUR BUSTER WILL THROW.

**CLAMP** – THE CLAMP IS DESIGNED FOR EASY HOOK-UP AND ADJUSTMENTS OF THE TOOL BAR ATTACHED IMPLEMENTS. THE UNIQUE DESIGN ENABLES YOU TO MOUNT INSIDE THE A FRAME AS WELL AS FORWARD AND UNDERNEATH THE TOOL BAR. TIGHTEN BOLTS SECURELY WHEN MOUNTING THE IMPLEMENTS. BE SURE THE JOINING TWO METALS ARE PARALLEL BEFORE DRAWING THE CLAMP BOLTS TIGHT.